NEUTRIK



# NMJ2HF-S

1/4" mono jack, unswitched, with a full threaded nose and standard solder lugs

Mounting nut included

## Features & Benefits

- Wide body and extremely durable contacts
- Mates with all mono A-gauge plugs acc. EIA RS-453 standard

## Technical Information

| Product | |
|---|---|
| Title | NMJ2HF-S |
| Connection Type | Jack |
| Gender | female |

| Electrical | |
|---|---|
| Contact resistance | < 15 mΩ |
| Dielectric strength | 1 kVdc |
| Insulation resistance | ≥ 1 GΩ @ 500 V dc |
| Rated current per contact | 3 A |


All rights reserved / 24.10.2026

NEUTRIK

| Mechanical | |
|---|---|
| Insertion force | < 30 N |
| Withdrawal force | 7 N |
| Lifetime | > 10000 mating cycles |
| Panel thickness | < 3 mm |
| Wiresize | |
| Wiring | Horizontal PCB mount |
| Locking device | Retention spring |
| Mounting direction | Rear mounting |
| Chassis shape | 11.2 mm |

| Material | |
|---|---|
| Cap / Nut / Washer | PA 6.6 15% GR |
| Contact plating | 2 µm Ag |
| Contacts | Bronze (CuSn6) |
| Shell | Polyamide (PA 6.6 30 % GR) UL 94 V0 |

| Environmental | |
|---|---|
| Standard compliance | EIA RS 453, IEC 60603-11 |
| Solderability | Complies with IEC 60068-2-20 |
| Temperature range | -25 °C to +70 °C |


All rights reserved / 24.10.2026