AUDOTA

AME-200

Amp modelling & Multi Effects

3.5-inch Color Display
Shows the effect chain, status values in different menu.

EDIT Encoder
Press or rotate it to select, toggle On/Off, adjust parameters.

MASTER
Adjust the master volume level.



SWITCH
Press to toggle On/Off selected effect module.

SAVE
Press to save settings.

PLAY
Press to enter PLAY mode.

BACK
Press to go back to last page or home display.

Footswitch A
- Press to switch to preset A in current bank in effect chain display;
- Press and hold to enter drum machine mode;
- Scroll down between drum grooves in drum machine mode;
- REC/DUB/PLAY in looper mode.

Footswitch D
Press to switch to preset D in current bank in effect chain display;
Press and hold to enter Tap Tempo mode;
Tap Tempo function in drum machine mode;
Tap Tempo function in looper mode.

Bank Down
Press footswitch A + B to scroll down between preset banks.

Footswitch B
- Press to switch to preset B in current bank in effect chain display;
- Press and hold to enter looper mode;
- Scroll Up between drum grooves in drum machine mode;
- STOP/DELETE for looper.

Footswitch C
- Press and hold to enter tuner;
- Play/Stop the drum machine in the drum machine mode;
- Play/Stop the drum machine in the looper mode.

Bank Up
Press footswitch C + D to scroll Up between preset banks.

EXP
¼ TR jack for external expression pedal.


OUTPUT
Dual ¼ mono audio jacks. Using both left and right output jacks simultaneously for stereo setup.

USB-C Port
Connect to AME200 computer software, OTG direct recording.

Input Level Meter
Shows the input level of the instrument signal.

Expression PedalMode Indicator
Displays whether thepedal is off, in volumemode, or wah mode.

Output Level Meter
Shows the output level of the left and right outputs.



Preset Area
Shows the preset number and preset name.



Effect Chain Area
Shows the loaded effect modules, and the On/Off status of effect modules in the effect chain.

Global BPM
Shows the value of global BPM. Utilize the EDIT to select and enter the BPM setting menu.

System Setting
Utilize the EDIT to select and enter the system setting menu.

INPUT
¼ audio jack connects to your instrument.

PHONE
1/8 stereo headphone output.

9V Power Port
Connect to the power supply comes with the pedal

Drum Machine
Utilize EDIT or press and hold footswitch A to enter Drum Machine menu.

Looper
Utilize EDIT or press and hold footswitch B to enter looper menu.

AUDOTA

AME-200

Amp modelling & Multi Effects

3.5英寸彩色显示屏
显示效果链等各界面功能信息。

EDIT编码器
可按下或旋转，实现功能选择、开关、参数编辑功能。

MASTER旋钮
控制总音量输出大小。



SWITCH按键
按下可开关效果链中的模块。

SAVE按键
按下保存预设参数。

BACK按键
按下返回上一界面和主界面。

PLAY按键
按下后大屏显示预设名称界面。

踩钉A
- 效果链界面按下切换至当前组预设A；
- 长按进入鼓机界面；
- 鼓机界面中执行鼓组下翻页；
- 录音循环界面中执行录音/叠录/播放。

预设组下翻页
按下踩钉A+B执行预设组下翻页。

踩钉B
- 效果链界面按下切换至当前组预设B；
- 长按进入录音循环界面；
- 鼓机界面中执行鼓组上翻页；
- 录音循环界面中执行暂停/删除。

踩钉C
- 效果链界面按下切换至当前组预设C；
- 长按进入调音表；
- 鼓机界面中执行鼓机开关；
- 录音循环界面中执行鼓机开关。


预设组上翻页
按下踩钉C+D执行预设组上翻页。

踩钉D
- 效果链界面按下切换至当前组预设D；
- 长按开启打点设速功能；鼓机界面中执行鼓机打点设速；
- 录音循环界面中执行鼓机打点设速。

EXP接口
“1/4”TRS外置踏板接口。

OUTPUT接口
双“1/4”单声道输出口，同时输出可实现立体声效果。

USB-C接口
用于连接PC端AME200软件和使用OTG录音功能。



INPUT接口
“1/4”乐器输入接口。

PHONES接口
“1/8”立体声耳机输出口。

9V电源接口
使用附带电源适配器连接电源。

输入电平提示
显示当前乐器输入音量大小。

踏板模式提示
显示踏板关闭或音量、哇音模式。

预设编号和名称显示
显示当前预设组和预设名称。



输出电平提示
显示左、右声道输出音量大小。

效果链编辑区域
显示当前效果链已加载模块和模块开关状态。

全局BPM设置
显示全局BPM值，可通过EDIT编码器进入BPM设置界面。

系统设置
使用EDIT编码器进入系统设置。

鼓机设置
使用EDIT编码器或长按踩钉A进入鼓机功能界面。

录音循环功能
使用EDIT编码器或长按踩钉B进入录音循环功能界面。