

Video > Processori e Gestione Video > Switcher e Matrici Video

Blackmagic Design ATEM Mini Extreme

Blackmagic Design ATEM Mini Extreme è un mixer video con 8 input, 2 output, ingressi ed uscite audio, connessione USB-C e HDMI.



Prezzo:	1.227,00 €
Disponibile:	Si
Consegna in:	4-5 giorni lavorativi
Spedizione:	Gratis in Italia
Marchio:	Blackmagic design
Categoria:	Switcher e matrici video
Condizione:	Nuovo
Link articolo	

Lo switcher avanzato per i professionisti. Ha tutte le funzioni di ATEM Mini Pro, più 8 ingressi HDMI, 2 uscite HDMI, 2 porte USB e una connessione per cuffie. Dispone anche di 4 chiavi cromatiche, 6 DVE per immagine nell'immagine, 2 lettori multimediali e un multiview fino a 16 riquadri.

Caratteristiche Blackmagic Design ATEM Mini Extreme

- Total Video Inputs: 8
- Total Outputs: 2
- Total Aux Outputs: 2
- Total Audio Inputs: 2 x 3.5 mm stereo mini jack.
- Total Audio Outputs: 1 x 3.5 mm stereo mini jack.
- Time Code Connection: None
- HDMI Video Inputs: 8 x HDMI type A, 10-bit HD switchable. 2 channel embedded audio.
- Video Input Re-Sync: On all 8 HDMI inputs.
- Frame Rate and Format Converters: On all 8 HDMI inputs.
- HDMI Program Outputs: 2
- Ethernet: Ethernet supports 10/100/1000 BaseT for live streaming, software control, software updates and direct or network panel connection.
- Computer Interface: 2 x USB Type-C 3.1 Gen 1 for external drive recording, webcam out, software control, software updates and panel connection.

Standards

- HD Video Input Standards: 720p50, 720p59.94, 720p60, 1080p23.98, 1080p24, 1080p25, 1080p29.97, 1080p30, 1080p50, 1080p59.94, 1080p60, 1080i50, 1080i59.94, 1080i60
- HD Video Output Standards: 1080p23.98, 1080p24, 1080p25, 1080p29.97, 1080p30, 1080p50, 1080p59.94, 1080p60
- Video Streaming Standards: 1080p23.98, 1080p24, 1080p25, 1080p29.97, 1080p30, 1080p50, 1080p59.94, 1080p60
- Ultra HD Video Standards: None
- Video Sampling: 4:2:2 YUV
- Color Precision: 10-bit
- Color Space: Rec 709
- HDMI Input Resolutions from Computers: 1280 x 720p 50 Hz, 59.94 Hz and 60 Hz. 1920 x 1080p 23.98, 24, 25,

Video > Processori e Gestione Video > Switcher e Matrici Video

29.97, 30, 50, 59.94 and 60 Hz. 1920 x 1080i 50, 59.94 Hz and 60 Hz

- Colorspace Conversion: Hardware based real time.

Product Specifics

- Upstream Keyers: 4
- Downstream Keyers: 2
- Advanced Chroma Keyers: Up to 4
- Linear/Luma Keyers: Up to 4
- Transition Keyer: DVE only.
- Total Number of Layers: 9
- Pattern Generators: 5
- Color Generators: 2
- DVE With Borders and Drop Shadow: 2
- Interface: Minimum monitor resolution of 1366 x 768.

Audio

- Audio Mixer: 11 input x 2 channel mixer.
- Selectable On/Off/Audio-Follow-Video per channel plus separate gain control per channel. Level and Peak metering. Plus new Fairlight audio enhancements: Compressor, Gate, Limiter, 6 bands of parametric EQ. Master gain control.
- Analog Input: Unbalanced stereo
- Analog Input Delay: Up to 8 frames
- Input Impedance: 1.8k
- Max Input Level: +6 dBV
- Mic Plug In Power: Available on both 3.5 mm mini-jack connections.

Streaming

- Direct Streaming: ATEM Mini Extreme supports direct live streaming using Real Time Messaging Protocol (RTMP) over ethernet or a shared mobile internet connection over USB?C.

Recording

- Direct Recording Video and Audio: USB-C 3.1 Gen 1 expansion port can record directly to external media.
- Video Recording: 1 x Program out as H.264 .mp4 file at the Streaming quality setting and at the ATEM video standard with AAC audio.
- Media Format: Supports media formatted ExFAT (Windows/Mac) or HFS+ (Mac) file system.
- Multi View Monitoring
- Multi View Monitoring: Configurable to 16, 13, 10, 7 or 4 up views including Program, Preview, 8 HDMI inputs, SuperSource, Clean Feed, Media Player, Streaming Status, Recording Status and Audio Meters.
- Multi View Video Standard: HD

Media Player

- Media Players: 2
- Channels: Fill and key for each Media Player.
- Media Pool Still Image Capacity: 20 with fill and key.
- Media Pool Still Image Format: PNG, TG A, BMP, GIF, JPEG and TIFF.

Power Requirements

Video > Processori e Gestione Video > Switcher e Matrici Video

- Power supply: 1 x External 12 V power supply.
- Power Usage: 36W