

Video > Hardware Video

Blackmagic Design Web Presenter HD

Blackmagic Design Web Presenter HD è un dispositivo per lo streaming in diretta attraverso ethernet e con un display frontale da 2,2".



Prezzo:	601,00 €
Disponibile:	Sì
Consegna in:	8-9 giorni lavorativi
Spedizione:	Gratis in Italia
Marchio:	Blackmagic design
Categoria:	Hardware video
Condizione:	Nuovo
Link articolo	

Blackmagic Web Presenter è la soluzione professionale completa con motore hardware di streaming per andare in diretta sulle piattaforme come YouTube, Facebook e Twitter tramite ethernet o la rete mobile di un telefono 5G o 4G. Le connessioni USB funzionano come le webcam: basta collegare un computer per usare qualsiasi software video. Vanta anche un'uscita per il monitoraggio tecnico con video, livelli audio e grafici di andamento.

Caratteristiche Blackmagic Design Web Presenter HD

- SDI Video Inputs: 1
- SDI Video Outputs: 1 x loop out, 1 x monitor out.
- SDI Rates: 1.5G, 3G, 6G, 12G
- HDMI Video Outputs: 1 x monitor out
- Webcam Output: 1 x Type USB-C
- Ethernet: Ethernet supports 10/100/1000 BaseT for live streaming, software control and software updates.

Standards

- HD Video Input Standards: 720p50, 720p59.94, 720p60, 1080p23.98, 1080p24, 1080p25, 1080p29.97, 1080p30, 1080p50, 1080p59.94, 1080p60, 1080PsF23.98, 1080PsF24, 1080PsF25, 1080PsF29.97, 1080PsF30, 1080i50, 1080i59.94, 1080i60
- Ultra HD Video Input Standards: 2160p23.98, 2160p24, 2160p25, 2160p29.97, 2160p30, 2160p50, 2160p59.94, 2160p60
- Video Input Color Space: Rec.601, Rec.709, Rec.2020
- 3G SDI: Auto detects SMPTE level A or B on SDI input.
- SDI and HDMI Monitor Out Video Standards: 1080p50, 1080p59.94, 1080p60
- Video Streaming Standards: 720p25, 720p30, 720p50, 720p60, 1080p23.98, 1080p24, 1080p25, 1080p29.97, 1080p30, 1080p50, 1080p59.94, 1080p60

Streaming

- Direct Streaming: Blackmagic Web Presenter HD supports direct live streaming over ethernet using Real Time Messaging Protocol (RTMP).
- Closed Captions: Web Presenter HD supports embedding CEA-608 and CEA-708 closed captions in your live RTMP stream.

Video > Hardware Video

Control

- Control Panel: Built in control panel with 2.2 inch color display for video preview, audio meters and status.
- Device Control: Front panel, USB?C or ethernet.

Software

- Compatible Services and Software: YouTube Live, Facebook Live, Twitter, Twitch, Skype, Open Broadcaster and Wowza Streaming Engine.

Operating Systems

- Mac 10.15 Catalina, Mac 11.1 Big Sur or later.
- Windows 10, 64-bit.
- Linux
- Chrome OS

Power Requirements

- Power supply: 1 x Internal 100 - 240V AC.
- 12 V_{DC} Input: 1 x +12 V DC 4?pin XLR.
- Power Usage: 21 W
- Environmental Specifications
- Operating Temperature: 0° C to 40° C (32° - 104°F)
- Storage Temperature: -20° to 45° C (-4° to 113° F)
- Relative Humidity: 0% to 90% non-condensing